













EN 685 & WICANDERS FLOORS

APPLICATION AREA vs. INTENSITY OF USE

	 DOMESTIC			 COMMERCIAL				 INDUSTRIAL	
	 1	 2	 3	 1	 2	 3	 4	 1	 2
	ECO CORK FLOORS (*)	CORK MASTER	WOOD-O-CORK	CORK-O-FLOOR	WOOD-O-FLOOR				
ECO CORK FLOORS (*)	Recommended	Recommended	Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended	Not Recommended
CORK MASTER	Recommended	Recommended	Recommended	Recommended	Recommended	Recommended	Not Recommended	Recommended	Recommended
WOOD-O-CORK	Recommended	Recommended	Recommended	Recommended	Recommended	Recommended	Not Recommended	Recommended	Recommended
CORK-O-FLOOR	Recommended	Recommended	Recommended	Recommended	Recommended	Recommended	Not Recommended	Recommended	Recommended
WOOD-O-FLOOR	Recommended	Recommended	Recommended	Recommended	Recommended	Recommended	Not Recommended	Recommended	Recommended

Recommended
 Not Recommended

Applies to Eco Cork Floors varnished after installation with 3 coats of W-2000

(*) Eco Cork Floors must be varnished after installation with min. 3 coats of W-2000, W-700 or W-800



S T R O N G F L O O R S B Y N A T U R E